



## SLK-97-TP

SEALED WITH INTEGRATED TOUCHPAD AND BACKLIGHTING

iKey's SLK-97-TP keyboard provides users with all the functionality of a full-size keyboard and mouse in a slim, compact package. It is designed for infection control in today's healthcare environment and for industrial applications. The fully sealed keyboard has an integrated touchpad and is compatible with all hospital-approved disinfectants. It is manufactured with red LED backlighting for use in low-light environments. The SLK-97-TP features left and right-click buttons below the touchpad, adding convenience and functionality. The durable and easily cleanable SLK-97-TP is ideal for use in ORs, medical carts and industrial workstations. Features: 12 Function Keys Cleanable, Liquidproof Design Integrated 10-Key Numeric Pad Red Backlit Keys USB configurations available

### Product Code SLK-97-TP

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 6ft
Key Switch	MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 210mA@5V (from Keyboard port) TOUCHPAD: 10 mA@5V (from Mouse port) USB: 220mA@5V (from CPU port)
Compatibility	PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 year limited warranty
Humidity	100% Humidity Resistant
Dimensions	14.44" x 5.40" x 0.89" (w-h-d) 366.8mm x 137.2mm x 22.6mm
Model Number	SLK-97-TP-PS2: With PS/2 cable SLK-97-TP-USB: With USB cable